

PRODUCT DATA

Date: February 2010

Code: 00654/30

IDENDEN T303 SELF-ADHESIVE BRIGHT FOIL TAPE

Idenden T303 Self-Adhesive Bright Foil Tape is the market leading product for the heating, ventilation and air conditioning and asbestos abatement sectors. The high standards of reliability, strength and durability mean it is now used for diverse applications in many other sectors, for example process plant, marine and offshore. Idenden T303 is manufactured to the highest specifications and is coated with a high tack rubber/resin adhesive system and protected by a removable release paper. Idenden T303 is the first choice of contractors and specifiers and is ideal for most HVAC applications. Idenden T303 provides unrivalled performance, maintaining insulation efficiency by protecting against the effects of fire, moisture and dust. It is easy to apply, exhibiting instant adhesion and can be moulded to any profile. The final bond has high shear strength and the foil promotes the optimum balance of surface conformity and tensile strength. This makes it ideal for lap sealing foil faced insulation materials, metal and duct sealing, asbestos abatement tenting and other general purpose applications.

Features

- High standards of reliability, strength and durability
- High tack adhesive
- Consistent performance over a wide temperature range
- Class 0 compliance

Product Characteristics

Finish	Bright aluminium foil
Adhesive	Rubber/resin
Release paper	High quality siliconised paper
Packaging	45m rolls in the following widths: 50mm x 24 rolls per carton 75mm x 16 rolls per carton 100mm x 12 rolls per carton
Shelf life/storage	At least 12 months from date of manufacture when stored in a dry place within the temperature range +10°C to +30°C.

Typical Performance Data (approx.)

Service temperature	-10°C to +90°C
Application temperature	-5°C (minimum)
Reaction to fire	Independently tested to BS 476 Part 6 – Pass Part 7 – Class 1 Building regulations – Class 0
Ultimate tensile strength (approx.)	80 N/25mm
Elongation (approx.)	8-11% (aluminium only)
Peel adhesion to steel (approx.)	<i>Initial:</i> 20-25 N/25mm <i>24 hours:</i> 25-30 N/25mm

Water vapour

ASTM B479 95 0.015 g/m²

Directions for use

IMPORTANT

Before embarking on any work involving Idenden T303 Self-Adhesive Bright Foil Tape, the separate Safety Data Sheet should be carefully studied by those carrying out the work.

1. Surfaces to be bonded must be clean, dry and free from dust, grease, oil and loose materials. If necessary, wipe surfaces sparingly with a cloth dampened with a ketone-free cleaner such as Evo-Stik Cleaner 4 and allow to dry for at least an hour before tape application.
2. The butt joints of insulation sections should be positioned together without gaps to ensure an adequate bond.
3. Select a tape width suitable for the application. A width of 50 mm is suitable for closely positioned, flat sections. Otherwise, select a tape the thickness of the insulation plus 50 mm to allow for the exposed cut edge.
4. Remove the release paper from a section of the tape, taking care not to touch the adhesive surface. Align the tape centrally over the joint. Pull the tape taut and then press down well over the entire joint area. Rub the tape to remove any wrinkles or folds.

NOTE: Idenden T303 Self-Adhesive Bright Foil Tape is intended for joint sealing applications only, and is therefore not suitable for use where the joint is subject to mechanical stress. In this instance, insulation should be fixed using a suitable adhesive or hanger system.

Precautions in Use

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate health and safety data sheet for Idenden T303 Self-Adhesive Bright Foil Tape.

See final page for disclaimer.

Bostik Limited, Common Road, Stafford, ST16 3EH, England

Tel: +44 (0)1785 272727

Fax: +44 (0)1785 257898

www.bostik.co.uk

Disclaimer - please read carefully

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company. Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Bostik Limited, Common Road, Stafford, ST16 3EH, England

Tel: +44 (0)1785 272727

Fax: +44 (0)1785 257898

www.bostik.co.uk